NANOLEX SISHIELD

Page: 1

Compilation date: 21.06.2019

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: NANOLEX SISHIELD

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers.

## 1.3. Details of the supplier of the safety data sheet

Company name: Infinitec GmbH

Matzenberg 171 Saarbrücken D-66115 Germany

Tel: +4968198 800306

Email: a.neuner@infinitec-gmbh.de

## 1.4. Emergency telephone number

Emergency tel: Medical Emergency information in case of poisoning: Poison Information Center Mainz -

24h - Phone: +49 (0) 6131 19240 (advisory service in German or English language)

## Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Flam. Liq. 3: H226; Skin Corr. 1B:

H314

Most important adverse effects: Flammable liquid and vapour. Harmful in contact with skin or if inhaled Causes severe

skin burns and eye damage. Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H312+H332: Harmful in contact with skin or if inhaled H314: Causes severe skin burns and eye damage. H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS05: Corrosion

GHS07: Exclamation mark







## NANOLEX SISHIELD

Page: 2

Percent

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P361+P364: Take off immediately all contaminated clothing and wash it before reuse.

**CLP Classification** 

#### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT / WEL

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

CAS

### 3.2. Mixtures

**EINECS** 

# Hazardous ingredients:

#### 2-BUTOXYETHYL ACETATE

203-933-3	112-07-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312	50-70%
N-BUTYL ACE	TATE			
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%
ORGANOPOL	ISILAZANE			
-	475645-84-2	-	Flam. Liq. 2: H225; Acute Tox. 4: H302;	10-30%

				H312; Acute Tox. 4: H312+H332; Acute Tox. 4: H332	
				11040 A . T . A 11040 11000 A .	
				Tox. 4: H302+H332; Acute Tox. 4:	
				Acute Tox. 4: H302+H312+H332; Acute	
				3: H412; Acute Tox. 4: H302+H312;	
				Skin Corr. 1B: H314; Aquatic Chronic	
'	-	475645-84-2	-	Flam. Liq. 2: H225; Acute Tox. 4: H302;	10-30%

## Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

NANOLEX SISHIELD

Page: 3

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

#### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool

containers.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

## 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## NANOLEX SISHIELD

Page: 4

#### Section 7: Handling and storage

## 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

## 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### **Hazardous ingredients:**

## 2-BUTOXYETHYL ACETATE

### Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	20 ppm	50 ppm	-	-

## **N-BUTYL ACETATE**

UK 724 mg/m3 966 mg/m3 -
--------------------------

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Colourless

Odour: Characteristic odour

NANOLEX SISHIELD

Page: 5

Flash point°C: 31

#### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

## 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

## Hazardous ingredients:

### 2-BUTOXYETHYL ACETATE

ORL	MUS	LD50	3200	mg/kg
ORL	RAT	LD50	2400	mg/kg

#### **N-BUTYL ACETATE**

ORL RAT LD50	10768 mg/kg
--------------	-------------

### **ORGANOPOLISILAZANE**

DERMAL	RBT	4H LC50	300-2000	mg/kg
ORAL	RAT	LD50	300-2000	mg/kg

#### NANOLEX SISHIELD

Page: 6

#### Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH DRM	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## **Section 12: Ecological information**

## 12.1. Toxicity

#### **Hazardous ingredients:**

#### **ORGANOPOLISILAZANE**

			$\overline{}$
	00111.050		
ZEBRAFISH (Brachydanio rerio)	96H LC50	57.1 ∣ ma/l	

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

## 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

# 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

## Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## NANOLEX SISHIELD

Page: 7

#### **Section 14: Transport information**

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

(2-BUTOXYETHYL ACETATE; N-BUTYL ACETATE)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 3

#### **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H302+H312: Harmful if swallowed or in contact with skin

H302+H312+H332: Harmful if swallowed, in contact with skin or if inhaled

H302+H332: Harmful if swallowed or if inhaled

## NANOLEX SISHIELD

H312: Harmful in contact with skin.

H312+H332: Harmful in contact with skin or if inhaled H314: Causes severe skin burns and eye damage.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.

Page: 8